




Características generales

- Conexión hembra: rosca de 1/2" a 4" (paralela)
- Apertura: rotación 90°.
- Manilla: palanca o mariposa.
- Cuerpo de bronce cromado.



Código	Gama	DN	ØA mm	B mm	C mm	D mm	E mm	gr	PN
FT80008014	1/4"	8	10	12.5	45	41	86	154	50
FT80008038	3/8"	10	10	13	47	41	86	158	50
FT80008012	1/2"	15	15	17	56	43	86	195	50
FT80008034	3/4"	20	20	18.3	67	46	86	297	40
FT80008100	1"	25	25	22	80	58	112	495	30
FT80008114	1" 1/4	32	32	24	94	63	112	700	25
FT80008012	1" 1/2	40	40	24	103	73	143	1070	20
FT80008200	2"	50	50	28.5	126	81	143	1755	20
FT80008212	2" 1/2	64	64	22	127	119	240	3060	15
FT80008300	3"	76	76	25	149	129	240	3970	15
FT80008400	4"	100	100	29	185.5	153	300	7835	15



ISO 9001
ISO14001


UniFit Paso Estandar

R.P.C. 



Características generales

- Conexión hembra: rosca de 1/2" a 4" (paralela)
- Apertura: rotación 90°.
- Manilla: palanca o mariposa.
- Cuerpo de bronce cromado.



Código	Gama	DN	ØA mm	B mm	C mm	D mm	E mm	gr	PN
FT14100002	1/4"	8	8	10.5	40	40.5	84	154	20
FT38100002	3/8"	10	10	10.7	43.8	36.8	89.5	158	20
FT12100002	1/2"	15	14	10.6	47	39.5	101	200	20
FT34100002	3/4"	20	18.5	11	53	42.5	101	300	20
FT01100002	1"	25	23	15	65	56	112	500	20
FT11400002	1" 1/4	32	29	14.5	73	62.5	132	740	20
FT11200002	1" 1/2	40	37	15.2	81	67	132	980	20
FT02200002	2"	50	47	16.8	98	91	161	1740	20
FT21200000	2" 1/2	64	64	23.5	136	113.5	225	3700	20
FT03300002	3"	76	75	26	151	119.5	225	5150	20
FT04400002	4"	100	97	27	180	139.5	225	8000	20



ISO 9001
ISO14001

Línea de Válvulas



Válvula Mez. 3 vías.

Válvula Bypass Sobrepresión

Válvula Reduc. de presión

Válvula Seguridad

Válvula Termost. mez. 5 vías

Válvula Termost. Seguridad

Válvula Mariposa

Válvula Motorizada

Válvula Mezcladora

(02) 430 7700

www.recal.cl · info@recal.cl · ventas@recal.cl